

## **AMENDMENTS TO THE CLAIMS**

Please cancel claims 33, 35, 37 and 38, as set forth in the listing of claims that follows:

### **Listing of Claims**

(insert listing of marked up claims)

1. (previously amended) An electronic assembly, comprising:  
a substrate;  
an electronic device having a first, second and third surface, said  
electronic device supported by said substrate;  
a heat pipe having a first and second segment, said first segment thermally  
coupled with said first surface of said electronic device;  
a thermal transient suppression material thermally coupled with said first  
segment of said heat pipe and at least said second surface of said electronic device, said  
material having a component capable of absorbing thermal energy by phase change from  
a solid to a liquid and said material being self contained, wherein said thermal transient  
suppression material includes sufficient thermal capacity for receiving transient thermal  
energy produced by said electronic device, and  
said heat pipe includes sufficient thermal capacity for receiving non-  
transient thermal energy produced by said electronic device and thermal energy received  
by said thermal transient suppression material;  
a heat dissipation device thermally coupled with said second portion of  
said heat pipe, wherein said heat dissipation device comprises a heat sink having cooling  
fins, and said heat sink comprises a first case portion; and

an elastomeric spring compressed between said first case portion and said first segment of said heat pipe, thereby maintaining said first portion of said heat pipe in thermal contact with said first surface of said electronic device.

2. (canceled)
3. (canceled)
4. (canceled)
5. (canceled)
6. (canceled)

7. (previously amended) The electronic assembly of claim 1, wherein said first case portion includes a recess, said recess receiving said elastomeric material.

8. (previously amended) The electronic assembly of claim 1, further comprising:

a second case portion, said second case portion being thermally conductive; and

a thermally conductive coupling member thermally coupling said third surface of said electronic device with said second case portion.

9. (original) The electronic assembly of claim 8, wherein said first surface and said third surface are located on opposite sides of said electronic device.

10. (original) The electronic assembly of claim 9, wherein said substrate defines an aperture and said thermally conductive coupling member protrudes through said aperture.

11. (original) The electronic assembly of claim 8, wherein said first case portion and said second case portion substantially enshroud said substrate and said electronic device therebetween.

12. (original) The electronic assembly of claim 11, wherein said first case portion and said second case portion further substantially enshroud said heat pipe.

13. (canceled)

14. (canceled)

15. (canceled)

16. (canceled)

17. (previously amended) The electronic assembly of claim 1, wherein said heat pipe includes a porous interior layer and liquid which is absorbable by said porous interior layer to provide heat conduction from said first segment to said second segment without requiring a mechanical pump.

18. (previously amended) The electronic assembly of claim 1, further comprising at least a second heat pipe thermally coupled with at least one of said first surface and said third surface of said electronic device.

19. (previously amended) The electronic assembly of claim 1,  
wherein said substrate includes a high current printed circuit board.

20. (previously amended) An electronic assembly, comprising:  
a high current circuit board;  
a first electronic device supported by said circuit board and having a first,  
second and third surface;

a heat conductive case having a first and second portion adjacent opposite  
sides of said circuit board;

a first heat pipe having a first segment thermally coupled with said first  
surface of said first electronic device and a second segment thermally coupled with said  
first case portion; and

a thermal transient suppression material in thermal contact with said  
second surface of said electronic device and said first segment of said first heat pipe,

wherein said thermal transient suppression material includes sufficient  
thermal capacity for receiving transient thermal energy produced by said first electronic  
device, and said first heat pipe includes sufficient thermal capacity for receiving non-  
transient thermal energy produced by said first electronic device and thermal energy  
received by said thermal transient suppression material, and

wherein said second case portion is in thermal contact with said third  
surface of said electronic device.

21. (canceled)

22. (canceled)

23. (canceled)

24. (previously amended) The electronic assembly of claim 20, wherein said first surface and said second surface are located on opposite sides of said electronic device.

25. (original) The electronic assembly of claim 24, further comprising a thermally conductive coupling member coupled between said second case portion and said third surface of said electronic device, and wherein said circuit board defines an aperture and said coupling member protrudes through said aperture.

26. (previously amended) The electronic assembly of claim 20, further comprising an elastomeric spring compressed between said first segment of said heat pipe and said first case portion.

27. (previously amended) The electronic assembly of claim 20, further comprising:

a second electronic device supported by said circuit board; and  
a second heat pipe having a first segment and a second segment, said first segment of said second heat pipe thermally coupled with said second electronic device.

28. (original) The electronic assembly of claim 27, wherein said second segment of said second heat pipe is thermally coupled with at least one of said first case portion and said second case portion.

29. (original) The electronic assembly of claim 28, wherein said first electronic device and said second electronic device are coupled to opposite sides of said circuit board.

30. (previously amended) The electronic assembly of claim 20, wherein said first electronic device includes electrically conductive leads and said thermal transient suppression material is thermally coupled with said leads.

31. (previously amended) The electronic assembly of claim 20, wherein at least one of said first and second case portions comprises cooling fins.

32. (previously amended) The electronic assembly of claim 20, further comprising at least a second heat pipe coupled with at least one of said first surface and said second surface of said first electronic device.

33. (canceled)

34. (canceled)

35. (canceled)

36. (original) An electronic assembly, comprising:  
a substrate;  
an electronic device having a first, second and third surface, said electronic device supported by said substrate;  
a heat pipe having a first and second segment, said first segment thermally coupled with said first surface of said electronic device;  
a thermal transient suppression material thermally coupled with said first segment of said heat pipe and at least said second surface of said electronic device, said material having a component capable of absorbing thermal energy by phase change from a solid to a liquid and said material being self contained; and

a thermally conductive coupling member coupling said first surface of said electronic device and said first segment of said heat pipe,

wherein said substrate defines an aperture and wherein said first surface of said device faces said aperture and said thermally conductive coupling member protrudes through said aperture.

37. (canceled)

38. (canceled)